## NSN 5305-01-241-2649

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-241-2649 **Thread Direction:** Right-hand **Thread Length:** Between 14.4 millimeters and 16.0 millimeters Fastener Length: 16.00 millimeters **Head Style:** Flat chamfer **Head Diameter:** Between 8.28 millimeters and 8.50 millimeters **Head Height:** Between 4.82 millimeters and 5.00 millimeters **Hole Diameter:** Between 1.20 millimeters and 1.35 millimeters **Internal Drive Style:** Hexagon **Thread Diameter:** 5.0 millimeters Width Across Flats: Between 4.03 millimeters and 4.15 millimeters **Hole Quantity:** 2 Hole Type: Drilled Min. Tensile Strength (psi): 113000 pounds per square inch **Thread Pitch In Millimeters:** 8.0 **External Thread Tolerance Class:** 6g **Hole Configuration Style:** Round internal hexagon Material: Steel **Surface Treatment:** Cadmium and chromate or zinc and chromate or aluminum and chromate **Surface Treatment Specification:** 

Qq-p-416 type 2 cl 2 federal specification 1st treatment response or mil-c-87115 cl 1 military specification 2nd treatment response or

**Thread Series Designator:** 

mil-c-83488 type 2 cl 2 military specification 3rd treatment response

Μ

Shelf Life:

N/a

## NSN 5305-01-241-2649

Socket Head Cap Screw - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-87115 spec.