# NSN 5305-01-241-2657

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-241-2657

# Thread Class: 3a

**Thread Direction:** 

Right-hand

# Fastener Length:

Between 0.617 inches and 0.637 inches

#### Head Style:

Knurled no. 1

#### Head Diameter:

Between 0.521 inches and 0.541 inches

#### Head Height:

Between 0.580 inches and 0.600 inches

# Internal Drive Style:

Slot

#### Material Accommodated Thickness:

Between 0.063 inches and 0.125 inches

Thread Diameter:

0.250 inches

#### Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

140000 pounds per square inch

#### **Special Features:**

Encapsulated 0 ring, metel 301, 304 cres, per mil-s-5059, o ring nitrile per mil-r-7362 type 2

#### Material:

Steel comp 302 spring

# Material Specification:

Qq-a-225/8 federal specification single material response stand-off

#### Surface Treatment:

Passivate spring

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

# Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

NSN 5305-01-241-2657

Panel Screw Assembly - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.

