NSN 5305-01-241-2657

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-241-2657 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.617 inches and 0.637 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.521 inches and 0.541 inches **Head Height:** Between 0.580 inches and 0.600 inches **Internal Drive Style:** Slot **Material Accommodated Thickness:** Between 0.063 inches and 0.125 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch **Special Features:** Encapsulated 0 ring, metel 301, 304 cres, per mil-s-5059, o ring nitrile per mil-r-7362 type 2 Material: Steel comp 302 spring **Material Specification:** Qq-a-225/8 federal specification single material response stand-off **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spring **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A003b0

NSN 5305-01-241-2657

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.