NSN 5305-01-241-3969

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-241-3969 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** Between 5.940 inches and 6.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.141 inches and 0.143 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch **Special Features:** Color black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 class 1 military specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-241-3969

Socket Head Cap Screw - Page 2 of 2



Ini	1 (Of	ΝЛ	മാ	e i	ırc	٠.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.