

View Online at <https://aerobasegroup.com/nsn/5305-01-241-3975>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.616 inches and 0.666 inches

**Fastener Length:**

Between 1.376 inches and 1.406 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.752 inches and 0.762 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.740 inches and 0.760 inches

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.251 inches first hole and 1.291 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0