NSN 5305-01-241-6289

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-241-6289 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.157 inches and 0.219 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.242 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Locking Feature:** Patch or pellet or strip **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Locking Feature Material:** Plastic polyamide **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches

Unjc

Thread Series Designator:

NSN 5305-01-241-6289

Machine Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0