3a

32

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-241-6290



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.345 inches and 0.438 inches Fastener Length: Between 0.407 inches and 0.438 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.221 inches and 0.226 inches **Head Height:** Between 0.074 inches and 0.086 inches Locking Feature: Pellet threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads **Product Name:** Navy special project Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1191 professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-241-6290

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

