NSN 5305-01-241-6303



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-241-6303 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.500 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.563 inches **Head Height:** Between 0.368 inches and 0.375 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.312 inches and 0.316 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Special Features:** Color black Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Oxide

Surface Treatment Specification:

Mil-c-13924 cl 4 military specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

6 type

NSN 5305-01-241-6303

Socket Head Cap Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Shelf Life:

Mil-std (military Standard): Mil-c-13924 spec.