## NSN 5305-01-242-0608



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-242-0608 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.258 inches and 1.380 inches **Fastener Length:** Between 1.320 inches and 1.380 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4140 or steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** 

Qq-p-416 type 2 cl 2 federal specification single treatment response

Color:

Black

**Thread Series Designator:** 

Unjc

**Specification Data:** 

80205-nas601 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-242-0608

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.