## NSN 5305-01-242-5959

Setscrew - Page 1 of 2



	0
View Online at https://aerobasegroup.com/nsn/5305-01-242-5959	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Fastener Length:	
Between 0.615 inches and 0.635 inches	
Head Style:	
Hexagon	
Head Height:	
Between 0.105 inches and 0.120 inches	
Width Between Flats:	
Between 0.305 inches and 0.314 inches	
Point Length:	
0.100 inches	
Point Diameter:	
Between 0.142 inches and 0.147 inches	
Point Style:	
Chamfer dog	
nternal Drive Style:	
Hexagon	
Thread Diameter:	
0.190 inches	
Width Across Flats:	
0.125 inches	
Thready Qty Per Inch (tpi):	
32	
Point Chamfer Angle:	
45.0 degrees	
Special Features:	
2 keyways in fastener 0.049 in. W by 0.044 in. Dp by 0.545 in. Lg, spaced 180 degrees apart	
Material:	
Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 304 or steel comp 304l or steel comp 305 or steel comp	308 or
steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp	316l or
steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385	
Material Specification:	
Qq-s-763 federal specification all material responses	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Qq-p-416, type 2 class 2 federal specification single treatment response	
Thread Series Designator:	
Jnf	

N/a

Shelf Life:

## NSN 5305-01-242-5959

Setscrew - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0