NSN 5305-01-242-7415

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-242-7415 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.313 inches **Head Height:** Between 0.185 inches and 0.190 inches **First Diameter From Head:** 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.688 inches **Internal Drive Style:** Hexagon **End Application:** Aircraft, hornet f/a-18 **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-01-242-7415

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0