NSN 5305-01-243-0755

Close Tolerance Screw - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5305-01-243-0755
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.378 inches and 0.428 inches
Fastener Length:
Between 1.763 inches and 1.793 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.477 inches and 0.492 inches
Head Height:
Between 0.140 inches and 0.150 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 1.365 inches and 1.385 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1578 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-243-0755

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0