Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-243-9172

3aThread Direction:Right-handThread Length:0.375 inchesFastener Length:0.375 inchesHead Style:ButtonHead Diameter:Between 0.201 inches and 0.213 inchesHead Height:Between 0.051 inches and 0.059 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:0.0625 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 45.0 rockwell cMaterial:SteelSurface Treatment:Oxide filmThread Series Designator:Unrc
Right-handThread Length:0.375 inchesFastener Length:0.375 inchesHead Style:ButtonHead Diameter:Between 0.201 inches and 0.213 inchesHead Height:Between 0.051 inches and 0.059 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:0.0625 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 45.0 rockwell cMaterial:SteelSurface Treatment:Oxide filmThread Series Designator:
Thread Length:0.375 inchesFastener Length:0.375 inchesHead Style:ButtonHead Diameter:Between 0.201 inches and 0.213 inchesHead Height:Between 0.051 inches and 0.059 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:0.0625 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 45.0 rockwell cMaterial:SteelSurface Treatment:Oxide filmThread Series Designator:
0.375 inches Fastener Length: 0.375 inches Head Style: Button Head Diameter: Between 0.201 inches and 0.213 inches Head Height: Between 0.051 inches and 0.059 inches Head Height: Between 0.051 inches and 0.059 inches Hexagon Thread Diameter: Ateral Diameter: 0.112 inches Width Across Flats: 0.0625 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Steel Surface Treatment: Oxide film
Fastener Length:0.375 inchesHead Style:ButtonHead Diameter:Between 0.201 inches and 0.213 inchesHead Height:Between 0.051 inches and 0.059 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:0.0625 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 45.0 rockwell cMaterial:SteelSurface Treatment:Oxide filmThread Series Designator:
0.375 inches Head Style: Button Head Diameter: Between 0.201 inches and 0.213 inches Head Height: Between 0.051 inches and 0.059 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: 0.0625 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film
Head Style:ButtonHead Diameter:Between 0.201 inches and 0.213 inchesHead Height:Between 0.051 inches and 0.059 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:0.0625 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 45.0 rockwell cMaterial:SteelSurface Treatment:Oxide filmThread Series Designator:
Button Head Diameter: Between 0.201 inches and 0.213 inches Head Height: Between 0.051 inches and 0.059 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: 0.0625 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film
Head Diameter:Between 0.201 inches and 0.213 inchesHead Height:Between 0.051 inches and 0.059 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:0.0625 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 45.0 rockwell cMaterial:SteelSurface Treatment:Oxide filmThread Series Designator:
Between 0.201 inches and 0.213 inches Head Height: Between 0.051 inches and 0.059 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: 0.0625 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film
Head Height:Between 0.051 inches and 0.059 inchesInternal Drive Style:HexagonThread Diameter:0.112 inchesWidth Across Flats:0.0625 inchesThready Qty Per Inch (tpi):40Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 45.0 rockwell cMaterial:SteelSurface Treatment:Oxide filmThread Series Designator:
Between 0.051 inches and 0.059 inches Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: 0.0625 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
Internal Drive Style: Hexagon Thread Diameter: 0.112 inches Width Across Flats: 0.0625 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
Hexagon Thread Diameter: 0.112 inches Width Across Flats: 0.0625 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
Thread Diameter: 0.112 inches Width Across Flats: 0.0625 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Steel Surface Treatment: Oxide film Thread Series Designator:
0.112 inches Width Across Flats: 0.0625 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
<ul> <li>Width Across Flats:</li> <li>0.0625 inches</li> <li>Thready Qty Per Inch (tpi):</li> <li>40</li> <li>Min. Tensile Strength (psi):</li> <li>160000 pounds per square inch</li> <li>Hardness Rating:</li> <li>36.0 rockwell c and 45.0 rockwell c</li> <li>Material:</li> <li>Steel</li> <li>Surface Treatment:</li> <li>Oxide film</li> <li>Thread Series Designator:</li> </ul>
0.0625 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
36.0 rockwell c and 45.0 rockwell c Material: Steel Surface Treatment: Oxide film Thread Series Designator:
Material: Steel Surface Treatment: Oxide film Thread Series Designator:
Steel Surface Treatment: Oxide film Thread Series Designator:
Surface Treatment: Oxide film Thread Series Designator:
Oxide film Thread Series Designator:
Thread Series Designator:
Lipro
Unic
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0