## NSN 5305-01-243-9348



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-243-9348 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.297 inches and 0.391 inches **Fastener Length:** Between 0.359 inches and 0.391 inches **Head Style: Button Head Diameter:** Between 0.298 inches and 0.312 inches **Head Height:** Between 0.077 inches and 0.087 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.0937 inches and 0.0947 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Material: Steel comp 1320 or steel comp 1330 or steel comp 3115 or steel comp 4012 or steel comp 4023 or steel comp 4130 or steel comp 4340 or steel comp 4427 or steel comp 8615 or steel comp 8740 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

**Demilitarization:** No

**Unit Of Measure:** 

N/a

## NSN 5305-01-243-9348

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0