

View Online at <https://aerobasegroup.com/nsn/5305-01-243-9415>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.250 inches

Fastener Length:

1.040 inches

Head Style:

Hexagon

Head Height:

Between 0.105 inches and 0.120 inches

Width Between Flats:

Between 0.367 inches and 0.375 inches

Internal Drive Style:

Slot

Material Accommodated Thickness:

Between 0.188 inches and 0.250 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

140000 pounds per square inch

Material:

Steel comp 301 secondary washer or steel comp 302 secondary washer or steel comp 302b secondary washer or steel comp 303 secondary washer or steel comp 303se secondary washer or steel comp 304 secondary washer or steel comp 304l secondary washer or steel comp 305 secondary washer or steel comp 308 secondary washer or steel comp 309 secondary washer or steel comp 309s secondary washer or steel comp 310 secondary washer or steel comp 310s secondary washer or steel comp 314 secondary washer or steel comp 316 secondary washer or steel comp 316l secondary washer or steel comp 317 secondary washer or steel comp 321 secondary washer or steel comp 347 secondary washer or steel comp 348 secondary washer or steel comp 384 secondary washer or steel comp 385 secondary washer

Material Specification:

Qq-a-225/8 federal specification single material response stand-off

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Mil-std (military Standard):

Mil-s-5059 spec.