## NSN 5305-01-244-3981

3a

32

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-244-3981



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.316 inches and 0.378 inches Fastener Length: Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches Locking Feature: Patch threads or pellet threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 63.0 microinches bearing surface of head Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1190 professional/industrial association standard Shelf Life:

N/a

## NSN 5305-01-244-3981

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

