## NSN 5305-01-244-5256

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-244-5256 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 0.933 inches and 0.963 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.336 inches and 0.381 inches **Grip Diameter:** Between 0.1891 inches and 0.1897 inches Single Shear Strength: 95000 pounds per square inch **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.625 inches and 0.645 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Stainless steel **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-244-5256

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0