## NSN 5305-01-244-8894

Between 0.356 inches and 0.392 inches

Between 1.372 inches and 1.392 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-244-8894

Head Style:
Flat countersunk
Head Diameter:
Between 0.328 inches and 0.385 inches
Locking Feature:
Detent ball grip
Grip Diameter:
Between 0.1889 inches and 0.1894 inches
Shank Unthreaded Hole Diameter:
0.070 inches second hole and 0.070 inches second hole
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 1.000 inches and 1.016 inches
Thready Qty Per Inch (tpi):
32
Hardness Rating:
43.0 rockwell c and 47.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
Special Features:
Retaining element in shank
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate

## NSN 5305-01-244-8894

Close Tolerance Screw - Page 2 of 2



Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0