

View Online at <https://aerobasegroup.com/nsn/5305-01-245-3569>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.360 inches and 0.390 inches

Fastener Length:

Between 0.922 inches and 0.954 inches

Head Style:

Knurled no. 2

Head Diameter:

Between 0.620 inches and 0.630 inches

Head Height:

Between 0.224 inches and 0.276 inches

Point Length:

Between 0.115 inches and 0.135 inches

Point Diameter:

Between 0.170 inches and 0.180 inches

First Diameter From Head:

Between 0.170 inches and 0.180 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.532 inches and 0.594 inches

Point Style:

Cone

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Externally Relieved Body Diameter Quantity:

1

Point Chamfer Angle:

Between 55.0 degrees and 65.0 degrees

Product Name:

Navy special project

Material:

Steel comp 203ez or steel comp 303 or steel comp 303 plus x or steel comp 303cu or steel comp 303ma or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 430fse

Material Specification:

Mil-w-52263 military specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-w-52263 spec.