NSN 5305-01-245-7182

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-245-7182

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.540 inches and 0.620 inches
Fastener Length:
Between 0.590 inches and 0.620 inches
Head Style:
Fillister
Head Diameter:
Between 0.166 inches and 0.183 inches
Head Height:
Between 0.072 inches and 0.079 inches
Hole Diameter:
0.037 inches
Internal Drive Style:
Slot
Thread Diameter:
0.112 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
62000 pounds per square inch
Screw Material:
Steel comp 1211
Screw Material Specification:
Qq-a-200/1 federal specification 1st material response or qq-a-225/6 federal specification 2nd material response
Screw Surface Treatment:
Anodize
Screw Surface Treatment Specification:
Mil-a-8625 type 1 military specification single treatment response or mil-a-8625 type 2 cl 1 military specification single treatment response
Head Hole Configuration Style:
Round
Thread Series Designator:
Unc
Specification Or Standard:
5s style and 1 type
Shelf Life:
N/a

NSN 5305-01-245-7182

Machine Screw - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.