## NSN 5305-01-246-0758

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-246-0758 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** Between 1.577 inches and 1.624 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.575 inches and 0.635 inches **Head Height:** Between 0.061 inches and 0.064 inches **Shoulder Diameter:** 0.3427 inches first shoulder and 0.3432 inches first shoulder **Shoulder Length:** 1.052 inches first shoulder and 1.072 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Surface roughness 32.0 micro inches; cetyl alcohol lube bolt only Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5305-01-246-0758

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0