NSN 5305-01-246-1808

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-246-1808
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.386 inches and 0.453 inches
Fastener Length:
Between 1.646 inches and 1.693 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.464 inches and 0.507 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Special Features:
Internal drive ribbed
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium or cadmium and chromate
Surface Treatment Specification:
Mas 672 assn standard 1st treatment response or mil-c-8837, type 2 class 2 military specification 2nd treatment response
Thread Series Designator:

Unjf

NSN 5305-01-246-1808

Close Tolerance Screw - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.