## NSN 5305-01-246-3840



Externally Relieved Body Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-246-3840 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.313 inches **Fastener Length:** Between 0.440 inches and 0.450 inches **Head Diameter:** 0.438 inches **Head Height:** 0.062 inches **First Diameter From Head:** 0.250 inches **Second Diameter From Head:** 0.145 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.070 inches and 0.075 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.132 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

Demilitarization: