NSN 5305-01-246-3847

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-246-3847 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.598 inches and 0.690 inches **Fastener Length:** Between 0.660 inches and 0.690 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5731 military specification 1st material response or ams5737 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas8101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A500d0

NSN 5305-01-246-3847

Machine Screw - Page 2 of 2



Mil-std (military Standard):

spec.