NSN 5305-01-246-9615

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-246-9615 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.193 inches and 0.213 inches Fastener Length: Between 0.650 inches and 0.680 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** Between 0.031 inches and 0.062 inches **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp 304 stand-off **Material Specification:** Mil-s-23195 military specification single material response stand-off **Surface Treatment:** Passivate stand-off **Surface Treatment Specification:** stand-off

Qq-p-35 federal specification single treatment response s
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-246-9615

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-23195 spec.