
NSN 5305-01-246-9615

Panel Screw Assembly - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.193 inches and 0.213 inches

Fastener Length:

Between 0.650 inches and 0.680 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.134 inches and 0.138 inches

Internal Drive Style:

Hexagon

Material Accommodated Thickness:

Between 0.031 inches and 0.062 inches

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.109 inches and 0.111 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 304 stand-off

Material Specification:

Mil-s-23195 military specification single material response stand-off

Surface Treatment:

Passivate stand-off

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stand-off

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5305-01-246-9615

Panel Screw Assembly - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

Mil-s-23195 spec.

