NSN 5305-01-247-2688

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-247-2688 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.683 inches and 0.750 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.155 inches and 0.167 inches **Head Height:** Between 0.053 inches and 0.062 inches **Locking Feature:** Pellet threads or patch threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1190 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-247-2688

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0