

View Online at <https://aerobasegroup.com/nsn/5305-01-247-3693>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.652 inches and 0.765 inches

**Fastener Length:**

Between 0.735 inches and 0.765 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.457 inches and 0.468 inches

**Head Height:**

Between 0.306 inches and 0.312 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.312 inches

**Width Across Flats:**

Between 0.250 inches and 0.253 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Minimum Yield Strength:**

30000 pounds per square inch

**Material:**

Steel comp 302 or steel comp 304 or steel comp 316 or steel comp xm-7 or steel comp 384

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Or Standard:**

6 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0