

View Online at <https://aerobasegroup.com/nsn/5305-01-247-3701>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.491 inches and 0.541 inches

Fastener Length:

Between 1.001 inches and 1.031 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.752 inches and 0.762 inches

Shoulder Diameter:

0.3896 inches first shoulder and 0.3901 inches first shoulder

Shoulder Length:

0.490 inches first shoulder and 0.510 inches first shoulder

Internal Drive Style:

High-torque

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Shoulder Shape:

Round first shoulder

Special Features:

Internal hexagon socket on threaded end 0.1582 in. To 0.1617 in. Width across flats

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0