NSN 5305-01-247-5866

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-247-5866 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.276 inches and 0.286 inches **Fastener Length:** 0.625 inches **Head Style:** Knurled no. 4 **Head Diameter:** 0.375 inches **Head Height:** Between 0.171 inches and 0.203 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.334 inches and 0.354 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a581 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qqp-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-247-5866

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0