

View Online at <https://aerobasegroup.com/nsn/5305-01-247-7602>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.132 inches and 0.199 inches

Fastener Length:

Between 0.219 inches and 0.250 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.147 inches and 0.172 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

80000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Head Surface Treatment:

Plastic epoxy

Head Surface Treatment Specification:

Mil-c-22750, class 1, type 2 military specification single treatment response

Shank Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Special Features:

Color gray fed-std 595 color no. 2655

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-22750 spec.