Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-248-1970

Thread Class:
3a
Thread Direction:
Right-hand
5
Thread Length: 1.375 inches
Fastener Length: Between 2.190 inches and 2.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.642 inches and 0.656 inches
Head Height:
Between 0.430 inches and 0.437 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.438 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-248-1970

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

