

View Online at <https://aerobasegroup.com/nsn/5305-01-248-4476>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.545 inches and 0.575 inches

**Fastener Length:**

Between 0.545 inches and 0.575 inches

**Head Height:**

0.188 inches

**Width Between Flats:**

0.197 inches

**Locking Feature:**

Lockwasher secondary washer

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Special Features:**

This screw is aprt Of a assembly that consist of 2-female screwlock, 4-washers, 2-nuts

**Material:**

Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1035 or steel comp 1040 or steel comp 1045 or steel comp 1050 or steel comp 1095 or steel comp 1213 or steel comp 1115 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1141 or steel comp 1144 or steel comp 1151 or steel comp 1214 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 1330

**Material Specification:**

Astm a108 assn standard all material responses

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astm b633 type 2 assn standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0