

View Online at <https://aerobasegroup.com/nsn/5305-01-248-5731>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.310 inches

Fastener Length:

0.500 inches

Head Style:

Flat countersunk undercut

Head Diameter:

0.385 inches

Head Height:

0.080 inches

Locking Feature:

Patch threads

First Diameter From Head:

0.134 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.110 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

80000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 302 fastener or steel comp 303 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener

Material Specification:

Fed-std66 federal standard all material responses fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Mil-f-14072 military specification single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.