

View Online at <https://aerobasegroup.com/nsn/5305-01-248-5731>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.310 inches

**Fastener Length:**

0.500 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

0.385 inches

**Head Height:**

0.080 inches

**Locking Feature:**

Patch threads

**First Diameter From Head:**

0.134 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.110 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 302 fastener or steel comp 303 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener

**Material Specification:**

Fed-std66 federal standard all material responses fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Mil-f-14072 military specification single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.