NSN 5305-01-248-7037



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-248-7037 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.502 inches and 0.579 inches **Fastener Length:** Between 1.829 inches and 1.876 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Mil-s-8695 military specification 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Screw Surface Treatment Specification:

Qq-p-416, type 2 class 3 federal specification single treatment
Thread Series Designator:

Unf
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No
Fiig:
A500d0

NSN 5305-01-248-7037

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-8695 spec.