NSN 5305-01-248-9795

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-248-9795 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 0.823 inches and 0.853 inches **Head Style:** Flat countersunk **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 108000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 63.0 microinches bearing surface of head Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1993 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-248-9795

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0