

View Online at <https://aerobasegroup.com/nsn/5305-01-249-0439>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 3.88 millimeters and 4.12 millimeters

**Fastener Length:**

Between 9.88 millimeters and 10.12 millimeters

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 5.5 millimeters and 5.8 millimeters

**Head Height:**

Between 1.65 millimeters and 1.90 millimeters

**First Diameter From Head:**

Between 2.10 millimeters and 2.35 millimeters

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 5.76 millimeters and 6.24 millimeters

**Internal Drive Style:**

Slot

**Thread Diameter:**

3.0 millimeters

**Thread Pitch In Millimeters:**

0.5

**External Thread Tolerance Class:**

6g

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 416

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, class 4 military specification single treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.