NSN 5305-01-249-0439

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-249-0439 **Thread Direction:** Right-hand Thread Length: Between 3.88 millimeters and 4.12 millimeters Fastener Length: Between 9.88 millimeters and 10.12 millimeters **Head Style:** Pan no. 2 **Head Diameter:** Between 5.5 millimeters and 5.8 millimeters **Head Height:** Between 1.65 millimeters and 1.90 millimeters First Diameter From Head: Between 2.10 millimeters and 2.35 millimeters Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 5.76 millimeters and 6.24 millimeters **Internal Drive Style:** Slot **Thread Diameter:** 3.0 millimeters **Thread Pitch In Millimeters:** 0.5 **External Thread Tolerance Class: Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 416 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 4 military specification single treatment response **Thread Series Designator:** М Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-249-0439

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.