## NSN 5305-01-249-3072



Close Tolerance Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-249-3072 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 1.079 inches and 1.109 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project **Special Features:** Tapped hole in head 0.1380-32, unjc-3b threads; distance from head top to injection port 0.290 in.; injection port 0.120 in. Lg, 0.060 in. W Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No Fiig:

A003b0

**Demilitarization:**