NSN 5305-01-249-8129

3a

32

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-249-8129



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.214 inches and 0.307 inches Fastener Length: Between 0.344 inches and 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.270 inches and 0.332 inches Locking Feature: Patch threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1189 professional/industrial association standard

NSN 5305-01-249-8129

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

