
Socket Head Cap Screw - Page 1 of 2





3a Thread Direction: Right-hand Thread Length: Between 0.282 inches and 0.375 inches Fastener Longth: Between 0.344 inches and 0.375 inches Head Style: Flat chamfer Head Sayle: Between 0.221 inches and 0.226 inches Head Height: Between 0.074 inches and 0.226 inches Head Height: Between 0.074 inches and 0.086 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thread Vity Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 32.0 microinches threads Material: 32.0 microinches threads Material: Striace Treatment Gadinum and chromate Cardinum and chromate Surface Treatment Specification: Gadinum and chromate	
Furead Direction:Right-handFuread Length:Between 0.282 inches and 0.375 inchesFastener Length:Between 0.344 inches and 0.375 inchesHead Style:Flat chamferHead Diameter:Between 0.221 inches and 0.226 inchesHead Height:Between 0.074 inches and 0.086 inchesLocking Feature:Strip threadsInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThread Diameter:0.138 inchesThread Style:1000 pounds per square inchMartinel Strength (psi):1300 pounds per square inchSurfacer Finish:0.100 pounds per square inchMartinel12.0 incincines threadsMartine:13.1 inches Iteradiet13.2 inches threadsHartinel Comp ed340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 613513.2 incheratiet13.2 indirectinetter13.2 indirectinetter13.2 indirectinetter13.2 indirectinetter13.3 indirectinetter13.3 indirectinetter13.4 indirectinetter13.5 indirectinetter13.6 indirectinetter13.7 indirectinetter13.8 indirectinetter13.8 indirectinetter13.9 indirectinetter13.0 indirectinetter13.0 indirectinetter13.0 indirectinetter13.0 indirectinetter13.0 indirectinetter13.0 indirectinetter14.0 indir	Thread Class:
Right-hand Thread Length: Between 0.282 inches and 0.375 inches Fastener Length: Between 0.344 inches and 0.375 inches Head Style: Flat chamfer Head Diameter: Between 0.221 inches and 0.226 inches Head Height: Between 0.074 inches and 0.086 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Oty Per Inch (tpi): 32 Min.Tensile Strength (psi): 160000 pounds per square inch Hardees 6.1 onchewell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Mineriii Stel comp	
Tread Length: Between 0.282 inches and 0.375 inches Fastener Length: Between 0.344 inches and 0.375 inches Head Style: Flat chamfer Head Diameter: Between 0.221 inches and 0.226 inches Head Height: Between 0.074 inches and 0.286 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready City Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 0.3.0 incickies threads Material: 32.0 microinches threads Material: 32.1 microinches threads Material: 32.2 microinches threads	
Between 0.322 inches and 0.375 inches Fastener Length: Between 0.344 inches and 0.375 inches Head Style: Flat chamfer Head Diameter: Between 0.221 inches and 0.226 inches Head Height: Between 0.074 inches and 0.086 inches Locking Feature: Stip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 32.0 microinches threads Material: 32.0 microinches threads Material: </td <td>-</td>	-
Fastener Length:Between 0.344 inches and 0.375 inchesHead Style:Flat chamferHead Diameter:Between 0.221 inches and 0.226 inchesHead Height:Between 0.074 inches and 0.086 inchesLocking Feature:Strip threadsInteract Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min Tensile Strength (psi):160000 pounds per square inchHardness Rating:0.130 rokeweil c and 4.0.0 rockweil cStripter Style:32.0 microinches threadsMarten:32.0 microinches threadsMarten:32.0 microinches threadsMarten:32.0 microinches threadsMarten:32.0 microinches threadsMarten:32.0 microinches threadsMerten:32.0 microinches threadsMarten:32.0 microinches threadsMarten:32.0 microinches threadsMarten:33.0 microinches threadsMarten:34.0 microinches threadsMarten:35.0 microinches threadsMarten:36.0 microinches threadsMarten:37.0 microinches threadsMarten:38.0 microinches threadsMarten:39.0 microinches threadsMarten:30.0 microinches threads30.0 microinches threads30.0 microinches threads30.0 microinches threads	-
Between 0.34 inches and 0.375 inches Head Style: Flat chamfer Head Diameter: Between 0.221 inches and 0.226 inches Head Height: Between 0.74 inches and 0.086 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 16000 pounds per square inch Hardness Rating: 32.0 microinches threads Stripter Einish: 32.0 microinches threads Metrial: 32.0 microinches threads Material: 33.0 microinches threads Material: 32.0 microinches threads Material:	
Head Style:Flat chamferHead Diameter:Between 0.221 inches and 0.226 inchesHead Height:Between 0.074 inches and 0.086 inchesLocking Feature:Dorking Feature:Corking Feature:Dirterad Diameter:Oross recess type 1Thread Diameter:0.138 inchesThready Cty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchHardinesSurface Finish:32. Oriscinches threadsMaterial:32. Oriscinches threadsMaterial:32. Oriscinches threadsMaterial:33. Oriscinches threadsMaterial:34. Oriscinches threadsMaterial:35. Orige Teatment36. Orischer BreadsMaterial:37. Orige Teatment38. Orige Teatment39. Orige Teatment39. Orige Teatment30. Orige Path (psi):30. Orige Path (psi):30. Orige Path (psi):30. Orige Path (psi):31. Orige Path (psi):32. Orige Path (psi):33. Orige Path (psi):34. Orige Path (psi):35. Orige Path (psi):36. Orige Path (psi):37. Orige Path (psi):38. Orige Path (psi):39. Orige Path (psi):39. Orige Path (psi):<	-
Flat chamfer Head Diameter: Between 0.221 inches and 0.226 inches Head Heigh: Between 0.074 inches and 0.086 inches Locking Feature: Dirth reads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 32.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 rockwell c and 40.0 rockwell c Burice Finish: 32.0 roic roinches threads Material: 32.0 roinc roinches threads Burice Finish: 32.0 roinc roinches threads Burice Finish: 32.0 roinc roinches threads Material: 32.0 roinc roinches threads Burice Treatment: 32.0 roinc roinches threads Burice Treatment: 32.0 roinc roinches threads 32.0 roinc roinches threads 33.	
Head Diameter:Between 0.221 inches and 0.226 inchesHead Height:Between 0.074 inches and 0.086 inchesLocking Feature:Strip threadsInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:32.Stricter Finish:32.Stricter Finish:32.Bet comp eds40 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp ed 150Surface Treatment:Cadmium and chromateFurder Treatment Specification:Cy-p-e16 type 2 cl 2 federal specification single treatment response	-
Between 0.221 inches and 0.226 inchesHead Height:Between 0.074 inches and 0.086 inchesLocking Feature:Strip threadsInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:32.32.Burder Einish:32.Burder Einish:32.Burder Einish:32.Burder Einish:33.34.Burder Einish:35.36.0 nockwell c and 40.0 nockwell cSurface Finish:37.38.Burder Einish:39.30.1 motion ches streadsMaterial:10.2 microin ches direadsSurface Treatment:10.3 microin ches direadsSurface Treatment:10.3 microin ches direads10.3 microin ches direads<	
Head Height: Between 0.074 inches and 0.086 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 32.0 microinches threads Material: Stel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Gurque-116 (type 2 cl 2 federal specification single treatment response	
Between 0.074 inches and 0.086 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness 8.01 cockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Stel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification Qu-p-416 type 2 cl 2 federal specification single treatment response	
Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 32.0 rickroiches threads Burtice Finish: 32.0 nickroiches threads Burtice Finish: 32.0 nickroiches threads Material: Stel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 Starface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response	Head Height:
Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 32.0 ricckwell c and 40.0 rockwell c Surface Finish: 32.0 nicroinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response	Between 0.074 inches and 0.086 inches
Internal Drive Style:Cross recess type 1Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cSurface Finish:32.0 microinches threadsMaterial:Stel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150Surface Treatment:Cadmium and chromateSurface Treatment Specification:Qr-p-416 type 2 cl 2 federal specification single treatment response	Locking Feature:
Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response	Strip threads
Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cSurface Finish:32.0 microinches threadsMaterial:Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150Surface Treatment:Cadmium and chromateSurface Treatment Specification:Qr.p-416 type 2 cl 2 federal specification single treatment response	Internal Drive Style:
0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response	Cross recess type 1
Thready Qty Per Inch (tpi):32Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cSurface Finish:32.0 microinches threadsMaterial:Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150Surface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl 2 federal specification single treatment response	Thread Diameter:
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Stel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response	0.138 inches
Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 40.0 rockwell cSurface Finish:32.0 microinches threadsMaterial:Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150Surface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl 2 federal specification single treatment response	Thready Qty Per Inch (tpi):
160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response	32
Hardness Rating:36.0 rockwell c and 40.0 rockwell cSurface Finish:32.0 microinches threadsMaterial:Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150Surface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl 2 federal specification single treatment response	Min. Tensile Strength (psi):
36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response	160000 pounds per square inch
Surface Finish:32.0 microinches threadsMaterial:Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150Surface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl 2 federal specification single treatment response	Hardness Rating:
32.0 microinches threadsMaterial:Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150Surface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl 2 federal specification single treatment response	36.0 rockwell c and 40.0 rockwell c
Material:Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150Surface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416 type 2 cl 2 federal specification single treatment response	Surface Finish:
Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response	32.0 microinches threads
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response	Material:
Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response	Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150
Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response	Surface Treatment:
Qq-p-416 type 2 cl 2 federal specification single treatment response	Cadmium and chromate
	Surface Treatment Specification:
Thread Series Designator:	Qq-p-416 type 2 cl 2 federal specification single treatment response
	Thread Series Designator:
Unjc	Unjc
Specification Data:	Specification Data:
80205-nas1191 professional/industrial association standard	80205-nas1191 professional/industrial association standard
	Shelf Life:
Shelf Life:	N/a
	Unit Of Measure:
Shelf Life:	
	Unit Of Measure:

NSN 5305-01-250-2191

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

