NSN 5305-01-250-6716

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-250-6716 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.615 inches and 0.682 inches **Fastener Length:** Between 1.375 inches and 1.422 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.7556 inches and 0.7604 inches **Head Height:** Between 0.1147 inches and 0.1167 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads **Special Features:** Supply with o ring, coat non bearing surface of head white Material: Stainless steel **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5305-01-250-6716

Close Tolerance Screw - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0