NSN 5305-01-251-1648

Between 0.523 inches and 0.559 inches

Between 1.289 inches and 1.309 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-251-1648

Head 9	Style:
Crown	ned hexagon
Head I	Height:
Betwe	en 0.189 inches and 0.204 inches
Width	Between Flats:
Betwe	en 0.559 inches and 0.564 inches
Lockir	ng Feature:
Detent	t ball grip
Grip D	Diameter:
Betwee	en 0.3737 inches and 0.3742 inches
Shank	c Unthreaded Hole Diameter:
0.106 i	inches first hole and 0.116 inches first hole
Intern	al Drive Style:
Slot	
Threa	d Diameter:
0.375 i	inches
Grip L	ength:
Betwee	en 0.750 inches and 0.766 inches
Thread	dy Qty Per Inch (tpi):
24	
Min. T	ensile Strength (psi):
90000	pounds per square inch
Hardn	ess Rating:
25.0 rc	ockwell c
Surfac	ce Finish:
32.0 m	nicroinches grip
Materi	ial:
Steel	comp xm-13
Materi	ial Specification:
Ams 5	629 assn standard single material response
Surfac	ce Treatment:
Passiv	vate
Surfac	ce Treatment Specification:
Qq-p-3	35 federal specification single treatment response

NSN 5305-01-251-1648

Close Tolerance Screw - Page 2 of 2



Thread	Series	Des	ignator	
Unjf				

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0