

View Online at <https://aerobasegroup.com/nsn/5305-01-251-3445>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.400 inches and 0.500 inches

Fastener Length:

0.500 inches

Head Style:

Flat chamfer

Head Diameter:

0.375 inches

Head Height:

Between 0.244 inches and 0.250 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

0.188 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 45.0 rockwell c

Special Features:

Verical knurls, color black

Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

Material Specification:

Sae grade 8 assn standard all material responses

Surface Treatment:

Oxide

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0