

View Online at <https://aerobasegroup.com/nsn/5305-01-251-3445>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.400 inches and 0.500 inches

**Fastener Length:**

0.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

0.375 inches

**Head Height:**

Between 0.244 inches and 0.250 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

0.188 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 45.0 rockwell c

**Special Features:**

Verical knurls, color black

**Material:**

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

**Material Specification:**

Sae grade 8 assn standard all material responses

**Surface Treatment:**

Oxide

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0