## NSN 5305-01-253-5908

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-253-5908 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.157 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.254 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 361 or steel comp comp 385 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A003b0

No