## NSN 5305-01-253-5918

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-253-5918 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.369 inches and 0.431 inches **Fastener Length:** Between 1.772 inches and 1.882 inches **Head Style:** Hexagon **Head Height:** Between 0.178 inches and 0.198 inches Width Between Flats: Between 0.367 inches and 0.375 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 175000 pounds per square inch **Hardness Rating:** 35.0 rockwell c primary washer and 43.0 rockwell c primary washer **Special Features:** Point length 0.205min and 0.235max Material: Steel comp xm-13 fastener **Material Specification:** Qq-s-763 federal specification all material responses stand-off **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-01-253-5918

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.