Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-253-7078

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.359 inches and 0.391 inches	
Fastener Length:	
Between 0.923 inches and 0.953 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.423 inches and 0.453 inches	
Head Height:	
Between 0.234 inches and 0.266 inches	
First Diameter From Head:	
Between 0.125 inches and 0.135 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
Between 0.553 inches and 0.573 inches	
Point Style:	
Cone	
Internal Drive Style:	
Slot	
Thread Diameter:	
0.190 inches	
Thready Qty Per Inch (tpi):	
32	
Externally Relieved Body Diameter Quantity:	
1	
Color:	
Black	
Material:	
Steel comp 303	
Material Specification:	
Astm a582 assn standard single material response	
Surface Treatment:	
Oxide	
Surface Treatment Specification:	
Mil-c-13924 military specification single treatment response	
Thread Series Designator:	
Unf	
Shelf Life:	
N/a	

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.