NSN 5305-01-254-2449

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-254-2449 **Thread Class:** 2a **Thread Direction:** Right-hand Fastener Length: 1.625 inches **Head Diameter:** Between 0.125 inches and 0.140 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response **Bearing Surface Of Head Surface Treatment:** Cadmium **Screw Surface Treatment:** Cadmium **Shank Surface Treatment:** Cadmium **Bearing Surface Of Head Surface Treatment Specification:** Mil-s-6050 military specification single treatment response **Head Surface Treatment Specification:** Mil-s-6050 military specification single treatment response **Screw Surface Treatment Specification:** Mil-s-6050 military specification single treatment response **Shank Surface Treatment Specification:** Mil-s-6050 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

Unit Of Measure:

N/a

NSN 5305-01-254-2449

Machine Screw - Page 2 of 2



Demi			

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.